




**VIEW B-B**  
**BOTTOM VIEW**



REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED



**SECTION A-A**



7	4	SCREW, SOCKET HEAD CAP	STK-01-321516370	1/2-13 X 2.5 Black Oxide
6	1	CONSTRUCTION BALL Ø.500 (CARR LANE #CL-3-SCB)	AME-MEC-01-2310	
5	2	THREADED DOWEL PIN - 1/2	AMF-87994	
4	45	SAFE PLASTIC HOLE PLUG 1/2-13	AMF-87944	
3	45	SAFE THREADED INSERT (1/2-13 ID x M18x1.5 OD x .87 LG.)	AMF-87321	
2	51	1/2" PRECISION BUSHING - (.5007/.5013 ID x 1/2 LG.)	AMF-80995	
1	1	BASE, AMROK 20° 3-SIDED PYRAMID, 300mm PALLET	AMR-PYR31205-20-50-D1	
ITEM NO.	QTY.	DESCRIPTION	PART NUMBER	ADDITIONAL DESCRIPTION

UNLESS OTHERWISE SPECIFIED		NAME		DATE		<div><div><b>ADVANCED</b> <b>MACHINE &amp; ENGINEERING CO.</b></div><div>2500 Latham St. Rockford, IL 61103 (815) 962-6076 (815) 963-4703 fax www.ame.com</div></div>					
DIMENSIONS IN INCHES		DRAWN		FS				2/14/2023			
FRACTIONAL ± 1/16 ANGLE: MACH ± 30' BEND ± 1°		CHECKED		SUN				2/14/2023			
		MATERIAL		ALUMINUM							
.0 ± .05 .00 ± .015 .000 ± .005 .0000 ± .0005		HEAT TREAT		-----		TITLE:  AMROK 20° 3-SIDED PYRAMID ASS'Y.					
		HARDNESS		-----							
FINISH = 125		REF. DWG		ORANGE ANODIZE		SIZE <b>B</b>		DWG. NO.  AMR-PYR31205-20-50		REV:  	
		DO NOT SCALE DRAWING									
BREAK ALL SHARP CORNERS .015"						SCALE: 1:4		WEIGHT [lbs]: 34		SHEET 1 OF 1	